Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

(Currently Amended) An image forming method comprising:
 laminating a plurality of toner layers on a surface of a transparent substrate electrophotographically;

subjecting fixing the plural toner layers to a primary fixing in ato the surface of the transparent substrate in a primary fixing step; and

subjecting fixing the primarily fixed the plural toner layers to in a secondary fixing step under lower pressure than the primary in a secondary fixing step to form a fixed image,

wherein the secondary fixing step is carried out under reduced pressure.

- 2. (Original) An image forming method according to claim 1, wherein the secondary fixing step is carried out in a non-contact manner.
- 3. (Original) An image forming method according to claim 1, wherein the secondary fixing step is carried out at 100 to 140°C.
- 4. (Currently Amended) An image forming method comprising according to elaim 1;

 laminating a plurality of toner layers on a surface of a transparent substrate electrophotographically;

 fixing the plural toner layers to the surface of the transparent substrate as a

primary fixing step; and
fixing the primarily fixed plural toner layers in a secondary fixing step under

wherein the secondary fixing step is carried by using heated rolls.

reduced pressure using heated rolls.

- 5. (Original) An image forming method according to claim 1, wherein the plural toner layers are heated under atmospheric pressure before the secondary fixing under reduced pressure in the secondary fixing step is carried out.
- 6. (Currently Amended) An image forming method according to claim 1, wherein the primary fixing step is carried <u>put out</u> at a primary fixing temperature of 100 to 145°C.

7. (Original) An image forming method according to claim 4, wherein a temperature of the heated rolls in the secondary fixing step is from 120 to 170°C.

- (Original) An image forming method according to claim 5, wherein the plural 8. toner layers are heated in a non-contact manner in an oven.
- (Original) An image forming method according to claim 5, wherein the plural 9. toner layers are heated at 80 to 140°C.

10.	(Currently Amended) An image forming method comprising according to
claim 1,<u>:</u>	
	laminating a plurality of toner layers on a surface of a transparent substrate
electrophoto	ographically;
	fixing the plural toner layers to the surface of the transparent substrate as a
primary fixi	ng step; and
	fixing the primarily fixed plural toner layers in a secondary fixing step under
reduced pre	ssure,
	wherein a degree of vacuum of the reduced pressure is no more than 1×10^4
Pa.	

- (Original) An image forming method according to claim 10, wherein the 11. secondary fixing step is carried out in a non-contact manner.
- (Original) An image forming method according to claim 10, wherein the 12. secondary fixing step is carried out at 100 to 140°C.
- (Original) An image forming method according to claim 10, wherein the 13. secondary fixing step is carried out by using heated rolls.
- (Original) An image forming method according to claim 10, wherein the 14. plural toner layers are heated under atmospheric pressure before the secondary fixing under reduced pressure in the secondary fixing step is carried out.
- (Original) An image forming method according to claim 10, wherein the 15. primary fixing step is carried out at a primary fixing temperature of 100 to 145°C.
- (Original) An image forming method according to claim 13, wherein a 16. temperature of the heated rolls in the secondary fixing step is from 120 to 170°C.
- (Original) An image forming method according to claim 14, wherein the toner 17. layers are heated in a non-contact manner in an oven.

- 18. (Original) An image forming method according to claim 14, wherein the toner layers are heated at 80 to 140°C.
- 19. (Original) An image-recorded medium formed by the steps comprising:

 laminating a plurality of toner layers on a surface of a transparent substrate electrophotographically;

fixing the plural toner layers to form a fixed image; and laminating the fixed image with a transparent laminate film, wherein the fixed image is formed by the image forming method according to claim 1.

20. (Original) An image-recorded medium produced by laminating a plurality of toner layers on a surface of a transparent substrate electrophotographically;

fixing the plural toner layers to form a fixed image; and laminating the fixed image with a transparent laminate film, wherein the fixed image is formed by the image forming method according to claim 10.